



iATTHEMO-B

True North Finding

Precise Heading, Attitude, Position & Velocity Reference based on Dual Antenna GNSS & MEMS IMU Data Fusion

iATTHEMO-B is a miniaturized dual-antenna GNSS compass with an integrated MEMS based inertial measurement system to provide true heading as well as attitude, velocity, position, angular rates and acceleration at high performance. It is a small size unit and easy to use.

- True Heading with up to 500 Hz data rate due to Dual Antenna GNSS, using L1L2 GPS, plus optional GLONASS
- Accurate roll, pitch, WGS84 position & velocity, rates and acceleration (integrated 42+ state INS/GNSS data fusion)
- Integrated odometer interface
- CAN / UART RS232 & RS422 / Ethernet TCP/IP and UDP and NMEA183 interfaces
- PPS output for synchronization

Due to its advanced architecture, iATTHEMO-B provides true north related heading even under such motion conditions, where other GNSS/ MEMS based systems fail (e.g. at standstill or motion with strong side slip angle). While standard GNSS based systems provide data only with low data rate, iATTHEMO-B

provides all data with up to 500 Hz and from standstill up to high dynamic conditions.

So, the iATTHEMO-B is a most suitable sensor, coming in a robust enclosure including strong EMI/ EMC filtering, to provide **Attitude, Heading and Motion** measurements for many surface, airborne, naval and automotive applications. As an option, the system is also available as single antenna version (iNAT-M200/SLC).



Furthermore with iATTHEMO-C a system is available which provides higher MEMS gyro performance than iATTHEMO-B and with iNAT-FSSG-1-DA also a more accurate dual-antenna system on FOG basis is available.

Technical Data of iATTHEMO-B (rms):

	Gyro Performance	Accelerometer Performance
Sensor Range:	± 450 °/s	± 18 g
Bias Stability (Allan Var.):	< 5 °/hr	0.1 mg
ARW / Noise:	0.26 °/ \sqrt{h}	0.07 mg/ \sqrt{Hz}
Bandwidth:	0...200 Hz	0...200 Hz
Scale Factor Accuracy:	0.1 %	0.1 %
Attitude / Heading Range:	± 180 ° Roll, ± 90 ° Pitch, ± 180 ° true heading (Yaw)	
Attitude Accuracy:	< 0.1 ° rms roll/pitch under sufficient motion with GNSS aiding ¹	
Heading:	< 0.4 ° rms true heading with 1 m antenna baseline and GNSS available ¹	
	< 0.2 ° rms true heading with 2 m antenna baseline and GNSS available ¹	
	< 0.1 ° rms under sufficient motion and sufficient GNSS availability ¹	
Attitude / Heading Resol./Drift:	< 0.01 °; < 0.01 °/s drift on heading/roll/pitch during short GNSS outages	
Position/Velocity:	using L1L2 GNSS based position / velocity Format: WGS84, up to 500 Hz data rate, performance: 1.5 m RMS (S/A off, no SBAS) Option -R: RTK accuracy (2 cm rms)	
Digital Output:	angular rate and acceleration, position in WGS84, velocity, Roll, Pitch, heading; BIT	
Integrated Features:	Dual-Antenna L1L2 GPS (option -G: additional GLONASS); IMU, 3D magnetometer, baro sensor, odometer interface as options	
Digital Interface:	CAN (up to 1 MBit/s), UART RS422 (up to 921.6 kbd), USB, Ethernet (TCP/IP, UDP)	
Output Data Rate, Connector:	up to 500 Hz via CAN / RS422; MIL-C-38999 III 37 pin; 2 x SMA for GPS antennas	
Temperature:	-40...+71 °C (case temperature); storage: -55...+85 °C	
Power:	9...34 V DC, approx. 8 W	
Size:	approx. W x L x H = 102 x 122 x 65 (metal case, IP65);	
Weight, Shock, Vibration:	approx. 800 grams; 60 g, 11 ms ; 20...2'000 Hz 5 g(rms) endurance	
Software:	iXCOM-CMD (under Windows and Linux available) for configuration and data storing	

iMAR Navigation GmbH • Im Reihersbruch 3 • D-66386 St. Ingbert / Germany
Phone: +49-(0)-6894-9657-0 • Fax: +49-(0)-6894-9657-22
www.imar-navigation.de • sales@imar-navigation.de

¹ under sufficient motion and with suitable GNSS aiding

